



Automatic Tilt Back Tyre Changing Machine for motorcycles, scooters & ATV Tyres

Automatic tilt back tyre changing machine for wheels with rim from 6" to 24" (max. wheel diameter 1110 mm./43", max. wheel width 240mm./9,5"). Suggested for motorcycle tyre specialists, servicing motorcycles, scooters and ATV tyres.

Main Features



Bike

Suitable for motorcycle wheels



Automatic

Model with four control pedals, tilting tower, sliding horizontal arm and operating arm with manual lowering and locking by pushing button.



6"-24"

Allows to operate with tyre assemblies from 6" to 24".



Jaw Clamping

Rim clamping is performed by means of 4 jaws facing each other, driven by pneumatic cylinders connected to the control pedal.



Blade Bead Breaking

Bead breaking by conventional blade, works with tyre assembly in vertical position



Description

Automatic tilt back tyre changing machine for wheels with rim from 6" to 24" (max. wheel diameter 1110 mm./43", max. wheel width 240mm./9,5").

Functions

- Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm;
- Bead breaker double effect Cylinder \varnothing 200 mm;
- Reinforced Chassis;
- Tabletop thickness 12 mm, specially designed for motorcycle wheels;
- Fitting head designed for both standard and low profiled tyre applications;
- Plastic protections on fitting head to avoid any damage to alloy rim;
- Four motorcycle clamping jaws adjustable to 4 different positions: 6"-13", 10"-17", 14"-21", 17"-24";
- Two powerful clamping cylinders provide uniform clamping pressure;
- Tyre inflation by pedal (optional);
- Suitable for Press Arm Eco (optional);
- "Easy Access" extractable pedal box for quick service.

Standard Features

Rim clamping range from outside	6" - 24"
Max. tyre diameter	1110 mm (43")
Max. tyre width	240 mm (9,5")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph / 220V - 1ph
Motor power	0,55 kW (3ph)
Rotating speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	225 Kg
Max overall dimensions	1170 x 1820 x 1910 mm



Standard accessories





QCBM (9238544)
Quick release kit for S116 Bike and S226 Bike shovel, including wider bead breaker shovel for bigger motorcycle tyre applications.



ATV-ADM (9215704)
Kit of 4 motorcycles adaptors with wider clamps, oversize height



MOTO-ADM (9215664)
Kit of 4 motorcycles adaptors with wider clamps, standard height.



SHIM (9215390)
Kit of 4 shims for wider clamps (only for **MOTO-ADM** and **ATV-ADM**)



PA ECO (9236722)
PRESS ARM ECO additional arm to ease mounting operations of low profiled and UHP tyres.



BAR-G (9298185)
CE inflating gauge



PSI-G (9299684)
Extra-CE inflating gauge.



PED-G (9236373)
Pedal operated inflating device.



HD (9208633)
Manual bead depressor.



PAD (9237711)
Manual bead depressor with extendable travelling pad.



Scan QR code to go to product web page



Giuliano Industrial S.p.A.

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



Social Network



Facebook



YouTube



Twitter



Giuliano Industrial S.p.A.